



INSTRUCTIONS FOR CONTINUED AIRWORTHINESS

Installation of RAM Exhaust Slip Joint p/n 1001-3 on Cessna 300 and 400 series Aircraft

Drawing 2688

October 26, 2006

Notice: (If Installed per STC # SA4331SW & SA4592SW)

This document must be referenced on Block 8 of FAA form 337 and added to the aircraft permanent record as required by 14 CFR Part 91, §91.417(a)(2)(vi) when the reference FAA-STC modification is accomplished on eligible aircraft. This document complies with the requirements of 14 CFR Part 23, §23.1529, in accordance with 14 CFR Part 23, Appendix G.

Aircraft Serial No. _____

Aircraft Registration No. _____

I. INTRODUCTION

This document provides instructions for continued airworthiness (ICA) for installation of RAM Slip Joint Assy. (part number 1001-3), on Cessna 300 and 400 series airplanes. These parts are approved via STC #SA4331SW & SA4592SW or PMA Supplement #126.

Updates to this document are available from RAM's Customer Service Department or online as follows.

RAM Aircraft, Limited Partnership
P O Box 5219
7505 Karl May Drive
Waco, TX 76708

Phone: 254 752-8381

Fax: 254 752-3307

Website: www.ramaircraft.com

II. DESCRIPTION

The RAM exhaust slip joint replaces the original exhaust joint on model 300 and 400 series Cessna aircraft. For specific FAA approved eligibility, refer to the RAM PMA supplement #126, the PMA tag or STC# SA4331SW & SA4592SW

III. SPECIAL PROCEDURES

None

IV. SERVICING INFORMATION

The following document shall be followed for installation of the Slip Joints on Cessna aircraft:

- Applicable FAA approved Cessna 300 or 400 series service and maintenance manual.
- Applicable FAA approved Cessna 300 or 400 series parts manual.

V. MAINTENANCE INSTRUCTIONS

The following document shall be followed for Parts, Overhaul, and Maintenance of the Slip Joints on Cessna aircraft:

- Applicable FAA approved Cessna 300 or 400 series service and maintenance manual.
- Applicable FAA approved Cessna 300 or 400 series parts manual.

VI. TROUBLESHOOTING

The following document shall be followed for Troubleshooting of the installation of the slip joint on Cessna 300 or 400 series aircraft:

- Applicable FAA approved Cessna 300 or 400 series service and maintenance manual.

VII. REMOVAL AND REPLACEMENT

The following document shall be followed for removal of the slip joints on the Cessna 300 or 400 series aircraft models:

- Applicable FAA approved Cessna 300 or 400 series service and maintenance manual.

The following document shall be followed for replacement of the slip joints on the Cessna 300 or 400 series aircraft models:

- Installation of RAM Slip Joints on Cessna 300 and 400 series airplanes should be done in accordance with RAM Drawing 1153, Revision M, dated October 17, 2006, or later FAA approved revision.

VIII. SPECIAL INSPECTION REQUIREMENTS

The following document shall be followed for inspection of the slip joint on Cessna 300 and 400 series aircraft models:

- Cessna Airworthiness Directive (AD) 2000-01-16, currently requires repetitively inspecting and replacing or repairing the exhaust system on certain Cessna Aircraft Company (Cessna) 300 and 400 series airplanes.

IX. APPLICATION OF SPECIAL TREATMENTS

None

X. DATA

- Exhaust Riser and Slip Joint Assy., RAM Drawing 1001, Revision X, dated October 17, 2006, or later FAA approved revision.
- Installation of RAM Slip Joints on Cessna 300 and 400 series airplanes should be done in accordance with RAM Drawing 1153, Revision M, dated October 17, 2006, or later FAA approved revision.

XI. SPECIAL TOOLS

None

XII. ADDITIONAL INFORMATION FOR COMMUTER CATEGORY AIRCRAFT

None

XIII. AIRWORTHINESS LIMITATIONS SECTION

Note: The airworthiness limitations section is FAA approved and specifies maintenance required under §§ 43.16 and 91.403 of the Federal Aviation Regulations unless an alternative program has been FAA approved.

Cessna Airworthiness Directive (AD) 2000-01-16, currently requires repetitively inspecting and replacing or repairing the exhaust system on certain Cessna Aircraft Company (Cessna) 300 and 400 series airplanes. This AD also revises the inspection intervals and requires replacing certain unserviceable parts and removing the exhaust system for a detailed inspection. The actions specified by this AD are intended to detect and correct cracks and corrosion in the exhaust system, which could result in exhaust system failure.

The same inspection procedures and criteria are applicable to RAM p/n 1001-3 slip joints as well. The method of compliance with AD 2000-01-16 for the RAM slip joints is the same as is stated in the AD.